

**40gpm Portable
Water Vacuum and Transfer**

The **PVAC** is your solution for high volume water capture and transfer, which eliminates the costly task of having to continually dump the collection tank. The Pvac is an ideal unit for flood and fire restoration contractors or as an excellent pick up system for wash contractors who are approved for sewer discharge.

POWER REQUIREMENTS	Requires: 115v / 20 amp or 5500w generator
POWER CORD	35' heavy-duty cord with GFCI for additional safety
HOPPER	Polyethylene, Conical Slant Bottom, 16 gallon capacity
FRAME	Stainless Steel frame with 10" air-filled tires
PORTABILITY	Designed for portable operation and mobility
SOLIDS SEPARATION	Gravity Separation with 1½" sludge/solids drain
VACUUM / PUMP OUT	Rate of 40gpm @ 50' away, and transfers water up to 200'
PUMP	Centrifugal pump with automatic pump out level control
VACUUM MOTOR	2 stage, 112cfm, 107" sealed lift vacuum, 115v 11.4amp
INLET	2" inlet, requires 2" vacuum hose
OUTLET	Set up for 1½", adaptable to ¾", requires discharge hose
WARRANTY	One Year Accessory Warranty
WEIGHT/DIMENSIONS	90# Dry Weight, 48" x 20" x 40"

Featuring:

- ✓ Non-corrosive, stainless steel frame
- ✓ Compact Design - Versatile and Portable, <100lbs.
- ✓ Wet / Dry Vacuum - Transfers up to 200' Away
- ✓ Automatic pump out level control
- ✓ High-water level vacuum safety shutoff

Options...

50' x 2" vacuum hose (DHV50), vacuum scupper (ATP75), sand berm (ZMAT6), Hydro Dike berm (ZMAT7), ground mountable vac dam (AVP), Hydro Vacuum Arch, 5' (ATP40)
Twister Vac (ANTV3 or ANT12) rotary surface cleaner/vacuum attachment

TO: _____

COMMENTS: _____

YOUR PRICE: _____

DISTRIBUTED BY:



HPI PROCESSES, Inc.
1030 Revenue Dr., Telford, PA 18969

Phone : 1-215-799-0450
Fax : 1-215-799-0459

Toll-Free : 1-888-733-2832
www.hpipro.com



The PVac is an excellent vacuum source for the Twister Vac accessory to recover the wash water as the twister is cleaning.

